

Rigel Led Street Light 19

The Rigel LED streetlight 19's slim design, is an excellent cost-effective street lighting solution for new construction or retrofit applications. The high output LED and PC lens provides outstanding uniformity and efficiency. Super smooth surface, avoids the accumulation of dust, sand or other materials, minimizing the environmental impact on the luminaire performance.



2 Lancaster Place
Electron Lane
Lanseria Corporate Estate
Lanseria
+2711(0) 4620251

genesis  ne
www.genesisonelightning.com
sales@genesisonelighting.co.za

Product Specification



LED Street Light

Product APPLICATIONS

Suitable for:
Street Lighting
Area Lighting
Parks
Parking lots
Recreational areas
Commercial area

Product FEATURES


Light weight, simple installation
High output lumen efficiency, 135lm/W.
Aluminum alloy housing construction.
Mounting options: Side entry .
Powder coating with strong anti-corrosion properties.
Three optional sizes 20W-150W.
Provided with 10KV Build-in Surge Protection Devices.
Intelligent function options including photocell, 1-10V dim, DALI dim, timer dim.
Reliability tests, including drop test, vibration test, and salt spray test.
Type II lighting distribution ensures adequate coverage for most applications




TECHNICAL DATA

MODEL NO.	SLN/ 02050019	SLN/ 03050019	SLN/ 05050019	SLN/ 07050019	SLN/ 09050019	SLN/ 12050019	SLN/ 15050019
WATT(W)	20	30	50	70	90	120	150
LUMEN	2 600	3 750	6 250	9 100	11 700	15 600	19 500
RATED INPUT VOLTAGE(V)	100-240VAC,			200-240VAC,			
SURGE PROTECTION	6kV line-line, 10kV line-earth						
POWER FACTOR	≥0.90						
EFFICACY (4000K, RA70)	130(±5%) LM/W						
CORRELATED COLOR TEMPERATURE	5000K (3000K, 4000K optional)						
COLOR RENDERING INDEX	Ra70 (Ra80 optional)						
BEAM ANGLE	Type II - Medium Range (R06302)			Type II - Medium Range (R11201)		Type II - Medium Range (R18401)	
IP RATING	IP66						
LUMINAIRE NETWEIGHT KG	2.0±0.3kg		2.2±0.3kg	3.1±0.2kg		4.0±0.2kg	
GROSS WEIGHT KG	2.5±0.3kg		2.7±0.3kg	3.9±0.2kg		4.9±0.2kg	
MATERIAL	Aluminium Alloy						
	Polycarbonate Optical Lens						
DIMMABLE	Non-dimmable (Dimmable optional 70-150W)						
FINISH	Powder Coating						
FINISHING COLOUR	Silver Grey						
LIFETIME (HR)	>50,000Hrs (Ta=30°C@L70)						
INTELLIGENT CONTROL	Photocell Control						
OPERATING TEMP.(°C)	-30°C ~ + 50°C						
MOUNTING OPTION	Side Pole Mounting						
PRODUCT DIMENSION	478×166×81mm			507.2*202.5*86.5mm		570.2*255.5*86.5m m	


Product Photometry



Product DIMENSIONS





Shorting cap



Note: If the luminaire use 5 pin or 7 pin photocell socket, it need to plus a waterproof gasket between socket and shorting cap.

Under the status of power-on, the light will not turn on without the shorting cap. It will turn on after installing the shorting cap.

Product INSTALLATION



Wall Mount Bracket



T Bracket



Pole Adaptor



L Bracket



Corner Mount